

## DA1N Spec sheet

Digital inputs	Superlink x 2 (BNC x 4 / D-Sub 9P x 1)
	USB(1.1) x 1
	AES/EBU (2P=hot) x 1
	COAXIAL x 1
	TOS x 1
Digital inputs sampling frequency	Superlink: 44.1kHz
	USB: 32 - 48kHz
	AES/EUB: 32 - 192kHz
	COAXIAL: 32 - 192kHz
	TOS: 32 - 96kHz
Digital filter	FLAT/PULSE selectable
$\Delta\Sigma$ -Over sampling frequency	32fs/64fs/128fs selectable
Sample rate converter	24bit/96kHz ON/OFF selectable (not available at Superlink/USB inputs nor with $\Delta\Sigma$ -Over sampling)
Frequency response	20Hz - 20kHz, -0.2dB (Digital filter FLAT)
S/N ratio	XLR -128dB, RCA -106dB (Sampling rate converter ON/A-weighted)
Analog outputs	Balanced XLR(2P=hot) x 1
	Unbalanced RCA x 1
Power	AC230V/120V, 50/60Hz (Specified on rear panel)
Power consumption	20W
Dimensions	Approx. 435(W) x 350(D) x 126(H)cm (Incl. Knobs, terminals and legs)
Weight	Approx. 14.5kg
Accessories	AC power cord, BNC cable x 4, Remote control, Battery x 2, Owner's manual
Color	Silver